



FOR DOORS OVER 4 SECTION TALL, ADD 2 STRUTS PER SECTION.

WIDTH	DOOR SIZE	P.S.F. TABLE	
		DESIGN PRESSURE	TEST PRESSURE
20'-0"	UP TO 12'-3"	+25.5	-28.5
18'-0"	UP TO 12'-3"	+31.5	-35.2
16'-0"	UP TO 12'-3"	+39.9	-44.5
14'-0"	UP TO 12'-3"	+45.6	-50.9
12'-0"	UP TO 12'-3"	+53.2	-59.3

NOTE: ALL NON-DESCRIPTIVE FASTENERS SHOWN TO BE 1/4"-20 X 5/8" HEX BOLTS & NUTS OR 1/4" X 3/4" LONG HEX HEAD SHEET METAL SCREWS.

Professional Engineer's seal provided only for verification of windood construction details.

John E. Scates PE
3121 FAIRGATE DR.
Carrollton, TX 75007
TX-PE 56308-F-2203
FL-PE-51737
(972) 492-9500

REV.	DATE	CHANGE
A	12/15/11	NEW LOGO/ENG. STAMP

MODELS:	730 724 426 735 750 755
PART NAME:	MODEL 730 "UP TO 20' WIDE"
MODEL:	W5 C
TOLERANCE	FRAC. ± 1/64" DEC. ± .015 ANG. ± 1'
SCALE	NONE
PLOT SCALE	SCALE
DATE:	12-03-09
DRN. BY	BNB
DWG. NO.	99-B-095
SHEET	1 OF 1

W WINDSOR DOOR

P.O. BOX 8915
LITTLE ROCK, AR
72219-8915
(501) 562-1872

FL 15080